



**File Name:** canon d5 manual.pdf

**Size:** 2268 KB

**Type:** PDF, ePub, eBook

**Category:** Book

**Uploaded:** 23 May 2019, 12:47 PM

**Rating:** 4.6/5 from 670 votes.

**Status:** AVAILABLE

Last checked: 9 Minutes ago!

**In order to read or download canon d5 manual ebook, you need to create a FREE account.**

[\*\*Download Now!\*\*](#)

eBook includes PDF, ePub and Kindle version

[Register a free 1 month Trial Account.](#)

[Download as many books as you like \(Personal use\)](#)

[Cancel the membership at any time if not satisfied.](#)

[Join Over 80000 Happy Readers](#)

### Book Descriptions:

We have made it easy for you to find a PDF Ebooks without any digging. And by having access to our ebooks online or by storing it on your computer, you have convenient answers with canon d5 manual . To get started finding canon d5 manual , you are right to find our website which has a comprehensive collection of manuals listed.

Our library is the biggest of these that have literally hundreds of thousands of different products represented.



## Book Descriptions:

# canon d5 manual

EOS M and EOS R Full Frame mirrorless ranges deliver the power of DSLR in the body of a compact camera. Register your product and opt in for exclusive offers and discounts. This page requires Javascript. Modify your browsers settings to allow Javascript to execute. See your browsers documentation for specific instructions. To install your download click on the name of the downloaded file.

Recommended Software	File Name	Date	File Size	Optional Software	File Name	Date	File Size
Recommended Manuals	File Name	Date	File Size	Optional Manuals	File Name	Date	File Size

The sole warranty, if any, with the respect to such nonCanon brand items is given by the manufacturer or producer thereof. This limited warranty covers all defects encountered in normal use of the Product, and does not apply in the following cases If the problem cannot be corrected over the telephone, you will be asked to follow the applicable procedures for MAILIN SERVICE. Note that a dated proof of purchase is required at the time of service. MAILIN SERVICE is a program under which your Product is repaired by a Canon U.S.A. or a Canon Canada authorized service center for the Product. Authorized service center information can be obtained by visiting [www.canontechsupport.com](http://www.canontechsupport.com) US customers only or by contacting the Canon U.S.A., Customer Care Center or Canon Canada Customer Information Centre at 1800OKCANON 18006522666. You will be given the name, address and phone number of an authorized service center. It is your responsibility to properly package and send the defective Product, together with a copy of your dated proof of purchase, a complete explanation of the problem and a return address to the authorized service center at your expense. Do not include any other items with the defective Product. The Product covered by this limited warranty and proven to be defective upon inspection will be repaired and returned to you without charge by the authorized service center. <http://www.gabident.pl/local/userfiles/3m-elipar-s10-manual.xml>

- **canon d5 manual, canon 5d manual, canon 5d manual pdf, canon 5d manual mode change aperture, canon 5d manual mark ii, canon 5d manual lens compatibility, canon 5d manual mark iii, canon 5d manual mode, canon 5d manual focus assist, canon 5d manual pdf download, canon d5 manual, canon d5 manual, canon r5 manual, canon m5 manual, canon t5 manual, canon t5 manual pdf, canon m5 manual download, canon m5 manual lens, canon m5 manual pdf download, canon d5 mark 4, canon d5 mark, canon d5 mark 2, canon d5 mark 5, canon d5 mark ii hdr, canon d5 mark iv sale, canon d5 mark 4 camera, canon d5 mark 4 reviews.**

Any Product received by the authorized service center that is not covered by the limited warranty will be returned unrepaired, or at the discretion of the authorized service provider, you may receive a written estimate of repair at such cost as the service center may establish from time to time. Scroll down to easily select items to add to your shopping cart for a faster, easier checkout. Visit the Canon Online Store It is designed to supply uninterrupted power for your camera. Kit includes the AC adapter, DC coupler and power cord. Adapter EcC, EdC Holds 12 Cameras bodies, 34 lenses and accessories. Inside measurements W x H x D 10 x 14.75 x 5 inches. Rugged nylon, waterrepellent, urethane coated for extra durability. Wellarranged divider system for secure storage and easy access. Lightweight construction, padded shoulder straps and back for comfort. Front webbing ideal for storing a light jacket. Tripod carrying straps. Color Black with Olive. Front and Rear zippered pouches. Zippered fulllength mesh pouch inside top cover. Divider system for secure storage and easy access. It is designed to hold two 35mm SLR bodies, 5 8 lenses, plus film and accessories. Can hold your cameras, lenses, accessories and even a laptop computer. Durable, waterrepellent nylon

exterior. Padded interior dividers and easyaccess storage pockets. The lens fits into the eyepiece holder of your EOS camera. Please see the Compatibility tab for a list of compatible EOS cameras. The lens fits into the eyepiece holder of your EOS camera. The lens fits into the eyepiece holder of your EOS camera. The lens fits into the eyepiece holder of your EOS camera. The lens fits into the eyepiece holder of your EOS camera. The lens fits into the eyepiece holder of your EOS camera. Requires Rubber Frame Ef, Eb or Ec. The lens fits into the eyepiece holder of your EOS camera. Made from Cordura Nylon. Large Zippered Front Accessory Pocket. <http://www.meselofalu.ro/userfiles/daewoo-frs2021ial-manual.xml>

Zippered Mesh Pocket Inside Top Lid. Two Side Accessory Zippered Pockets. Tripod Loops on Bottom. Five Movable, Padded Internal Dividers. Two Strap Handles with Grip. Removable Shoulder Strap. Rubber Feet for Ground Protection. The strap attaches to the eyelets at the sides of the camera. The cable connects to your camera and to the USB port on your PC or MAC Computer. Comes standard with the EOS 1Ds Mark III, 1D Mark IV, 1D Mark III, 1Ds Mark II, 1D Mark II N, 1D Mark II, 5D Mark II, 7D, 5D, 50D, 40D, 30D, 20D, 10D, Digital Rebel XTi, Digital Rebel XT and Digital Rebel. Please see Compatibility tab for compatible models. Features adjustable tripod straps, and high strength buckles for the main compartment. The Canon logo is embroidered on the top flap. The Remote Switch works just like a shutter button, enabling halfway or complete pressing. This remote switch has a selftimer, interval timer, long exposure timer and exposurecount setting feature. The timer can be set from 1 second to 99 hours. A new dial enables you to easily enter the numeric settings with a single thumb. There are two versions of the EDSDK compatible with Windows or Macintosh. If the camera or memory card is faulty and the images cannot be recorded or read by a personal computer, Canon cannot be held liable for any loss or inconvenience caused. Copyrights Copyright laws in your country may prohibit the use of your recorded images of people and certain subjects for anything but private enjoyment. Please purchase it separately. Doing so may cause fire or a health hazard. If the product does not work properly or requires repair, contact your dealer or your nearest Canon Service Center. If you accidentally drop the camera into water, promptly consult your nearest Canon Service Center. Wipe off any water droplets with a dry cloth. If the camera has been exposed to salty air, wipe with a wellwring wet cloth. Always store your CF cards in a case to protect the data stored on them.

NonCanon CF cards may not be able to record and playback images. Using Canon CF cards is recommended. To recharge the battery, see page 22. Attach the lens. p.27 Align the red dot. Set the lens focus mode switch to. p.27 Open the cover and insert a CF card. p.28 Face the label side toward you and insert the end with the small holes into the camera. Focus the subject. Aim the AF point over the subject and press the shutter button halfway to autofocus. Be sure it is set to. Attaching the Strap Pass the end of the strap through the camera's strap mount from the bottom. Then pass it through the strap's buckle as shown in the illustration. When you remove the battery from the camera, be sure to reattach the cover to protect against short circuit. Attach the battery. Align the battery front edge with the mark on the battery charger. While pressing down the battery, slide it in the direction of the arrow. Using them with a nonCanon battery charger or product may result in malfunction or accidents for which Canon cannot be held liable. After the red lamp lights, continue to recharge the battery for an hour to attain a full charge. Battery Pack BP514, BP511, or BP512 can also be used. Checking the Battery Level When the switch is set to or p.30, the battery level will be indicated at one of four levels. The actual number of shots may be fewer than indicated above depending on the shooting conditions. Do not connect or disconnect the power cord while the camera's switch is set to. Remove the caps. Remove the rear lens cap and the body cap by turning them as shown by the arrow. Insert the CF card. Using Canon CF cards is recommended. If the CF card is inserted in the wrong way, it may damage the camera. As shown by the arrow,. While the access lamp is lit or blinking, do not do any of the following. Doing so may damage the image data, CF card, or camera. To save battery power, the camera turns off automatically after 1 minute of non

operation.

To turn on the camera again, press the shutter button or other button. If you press the shutter button completely without pressing it halfway first or if you press the shutter button halfway and then press it completely immediately, the camera will take a moment before it takes the picture. You can also operate 1 when the switch is set to. Operating the. While looking at the LCD monitor, you use the button, button, and dial on the camera back to proceed to the next step. The explanation of menu functions hereinafter assumes that you pressed the. The Language screen will appear. Set the desired language. Turn the dial to select the language, then press. Each captured image is recorded with the date and time it was taken. Make sure you set the date and time correctly. If any dust adheres on the image sensor, it may show up as a dark speck on the images. To avoid this, follow the procedure below to clean the image sensor. Using the AC Adapter Kit ACKE2 optional, see page 166 is recommended. If you cannot remove all of the dust, consult a Canon Service Center. 3 Cleaning the CMOS sensorN Clean the image sensor. If the camera's dioptic adjustment still cannot provide a sharp viewfinder image, using Dioptic Adjustment Lens E 10 types, optional is recommended. The mode automatically sets the AF mode, drive mode, etc. All you do is point and shoot. In addition, to help prevent mistakes caused by operating the camera improperly, the. With nine AF points to focus the subject, anyone can easily take nice pictures. AF point Focus confirmation light Shutter speed Aperture Set the Mode Dial to. Replace the CF card with one that has room. Using a nonCanon lens with an EOS camera may not result in proper camera or lens operation. Do not stand in front of the camera when you press the shutter button to start the selftimer. Doing so will throw off the focus. Use a tripod when you use the selftimer. To cancel the selftimer after it starts, press the.

In the 1 mode, the captured image will require postprocessing with the software provided. Burst During Continuous Shooting The maximum burst during continuous shooting depends on the image recording quality. The approx. maximum burst during continuous shooting is indicated below for each imagerecording quality. Note that with highspeed CF cards, the maximum burst may be higher than shown in the table below depending on the shooting conditions. You can also adjust the settings of each Picture Style to obtain custom image effects. This is the Picture Style used in the. To obtain naturallooking, blackandwhite images, set a suitable white balance. The setting screen will appear. A color can be brightened by using a filter having a similar or same color. At the same time, the complementary colors will be darkened. You can also select a Picture Style already set with the provided software. If you do not want to change the User Defined Picture Style, do not repeat this procedure. A higher ISO speed number indicates a higher sensitivity to light. Therefore, a high ISO speed is suited for low light and moving subjects. However, the image may look more coarse with noise, etc. With a digital camera, the color temperature can be adjusted with software so that the colors in the image look more natural. The subject's white color is used as the criteria for adjusting the other colors. By selecting this image, you import its white balance data for the white balance setting. Spot metering Photograph a white object. This adjustment will have the same effect as using a color temperature conversion or color compensating filter. Each color can be corrected to one of nine levels. Users familiar with using color temperature conversion or color compensating filters will find this feature handy. This is called white balance bracketing. With this camera, you can set the color space for captured images to sRGB or Adobe RGB. For normal images, sRGB is recommended.

In the Full Auto mode, sRGB will be set automatically. This is optional since a folder will be created automatically for saving captured images. Creating a Folder A folder can have up to 9999 images. If the active folder reaches 9999 images, a new folder will be created automatically to save images captured thereafter. Creating Folders with a Personal Computer With the memory card open on the screen, create a new folder named "Dcim." Open the Dcim folder and create as many folders as necessary to save and organize your images. The images you take are automatically assigned a file number from 0001 to 9999. Since the file number starts from 0001 in each CF card, you can

organize images according to CF card. Note that if the replacement CF card already contains images, the file numbering will start after the highest file number in that CF card. Camera Setting Display Auto power off p.39 File number p.70 CF card remaining capacity Folder number p.68 Flash exposure compensation p.100 For details on the image info. The AF mode, AF point selection, metering mode, and drive mode will be set automatically in the. Three AF modes are provided. OneShot AF is suited for still subjects, while AI Servo AF is for moving subjects. And AI Focus AF switches from OneShot AF to AI Servo AF automatically if the still subject starts moving. If this occurs, a picture cannot be taken even if the shutter button is pressed fully. Recompose the picture and try to focus again. This is for obtaining correct focus at the moment of exposure. The AF point can be selected automatically by the camera or manually by you. In the Full Auto mode, automatic selection will be set. Automatic AF point selection The camera selects the AF point automatically according to the shooting conditions. This is called "focus lock." Focus lock works only in the OneShot AF mode. If the AF mode is AI Servo AF or AI Focus AF set to Servo mode, focus lock will not work.

In the Full Auto mode, evaluative metering is set automatically. In the Full Auto mode, single shooting is set automatically. During continuous shooting, the captured images are first stored in the camera's internal memory and then successively transferred to the CF card. When the internal memory becomes full during continuous shooting, "buSY". The asterisk M appended on the right of the page title indicates that the respective feature cannot be changed in the. The camera automatically sets the shutter speed and aperture value to suit the subject's brightness. Increase the ISO speed or use flash. If "8000" and the minimum aperture blink, it indicates overexposure. Decrease the ISO speed or use an ND filter optional to reduce the amount of light entering the lens. This is called ShutterPriority AE. A fast shutter speed can freeze the motion of a fastmoving subject and a slow shutter speed can blur the subject to give the impression of motion. Turn the dial to set a slower shutter speed until the aperture value stops blinking. If the minimum aperture blinks, it indicates overexposure. Turn the dial to set a faster shutter speed until the aperture value stops blinking or lower the ISO speed. This is called aperturepriority AE. If the "8000" shutter speed blinks, it indicates overexposure. To determine the exposure, refer to the exposure level indicator in the viewfinder or use a handheld exposure meter. This method is called manual exposure. Set the exposure. Check the exposure level and set the desired shutter speed and aperture value. You can make the image look lighter increased exposure or darker decreased exposure. Increased exposure Decreased exposure The exposure compensation amount will remain in effect even after the. This is called Auto Exposure Bracketing AEB. Standard exposure AEB amount Standard exposure Decreased exposure Increased exposure Decreased exposure.

If the drive mode is set to continuous i, the three bracketed shots will be taken continuously and then the shooting will stop automatically. If the drive mode is set to single image u, you must press the shutter button three times. After locking the exposure, you can recompose the shot while maintaining the desired exposure setting. This is called AE lock. It is effective for backlit subjects. This is called bulb exposure. Use bulb exposures for night scenes, fireworks, the heavens, and other subjects requiring long exposures. This prevents mirror vibrations which may blur the image during closeups or when a super telephoto lens is used. During a bulb exposure, pressing the shutter button completely will turn off the LCD panel illumination. However, you can turn on the illumination for 6 sec. CF Card Reminder This prevents shooting if there is no CF card in the camera. This can be set in all shooting modes. For details on using the EXseries Speedlite, refer to the Speedlite's instruction manual. The EOS 5D is a TypeA camera compatible with all EXseries Speedlites providing the features below. Since connection cords are unnecessary, flexible and sophisticated lighting setups are possible. Only with wirelesscompatible Speedlites. TTL and ATTL Autoflash Speedlites With TTL and ATTL autoflash Speedlites EZ, E, EG, ML, TL series set in the TTL or ATTL autoflash mode, the flash will be fired. For images taken with another camera The camera might not be able to properly

display images captured with a different camera or edited with a personal computer or whose file name was changed. If you press the. The brightness adjustment screen will appear. You can view a single image, the shooting information, an index display, or a magnified view. The horizontal axis indicates the brightness level darker on the left and brighter on the right, while the vertical axis Dark image indicates how many pixels exist for each brightness.

Switching from the index display to another display format To display a single image, press the button. Pressing the button switches to the single image display and pressing it again switches to magnified view. Magnified area During the magnified view, you can turn the or dial to view the next or previous image at the same magnification and scroll position. With C.Fn181 set, you can hold down the. Each image will be displayed for about 3 sec. During auto play, auto power off will not work. The display time may vary depending on the image. During auto play, you can press the. Images will then be displayed in the correct orientation during playback. You can rotate the image even after you change the display format to shooting info display, magnified view, or index display after step 1. Jump bar Single Image and Information Display During the single image and information display, you can use the Jump feature by 10 or 100 images, date, or folder. Or turn it counterclockwise to jump backward by 10 or 100 images. Jump shot date You can jump to a picture taken on a specific date. Always turn off the camera and the television before connecting or disconnecting them. Video IN terminal If the proper video system format is not set, the image will not be displayed properly. Image protect icon Once an image is protected, it cannot be erased by the camera's Erase function. To erase a protected image, you must first cancel the protection. If you erase all the images p.119, only the protected images will remain. This is convenient when you want to erase unnecessary images all at once. Only protected images will not be erased. Once an image is erased, it cannot be recovered. Make sure you no longer need the image before erasing it. To prevent important images from being erased accidentally, protect them. A nonCanon CF card or a CF card formatted with another camera or personal computer might not work with the camera. If this happens, format the card with the camera first.

The camera enables direct printing with printers compatible with " PictBridge", Canon " CP Direct", and Canon " Bubble Jet Direct.". For direct printing, using AC Adapter Kit ACKE2 optional to power the camera is recommended. Refer to the table Printers and Cables below to select the proper cable to connect the camera to printer. If you use a battery to power the camera, make sure it is fully charged. During direct printing, keep checking the battery level. If there is a long beeping sound in step 5, it indicates a problem with the PictBridge printer. Some settings might be disabled. For details, refer to your printer's instruction manual. Check that the icon is displayed on the upper left of the LCD monitor. Turn the. Image Borders Date Set the number of copies. Turn the dial to select the menu item, then press. Turn the dial to select the desired setting, then press. The image will also be cut off along all four edges. Check that the icon is displayed on the upper left of the LCD monitor. Turn the. Turn the dial to select the menu item, then press. The date will appear on the lower right of the image. Do the trimming right before printing. If you set the trimming and then set the print settings, you may have to set the trimming again. The smaller you make the trimming frame, the grainier the picture will look. If the picture will be too grainy, the trimming frame will turn red. While trimming the image, look at the camera's LCD monitor. To use the same settings again, follow the steps below. With Easy Printing, only one print can be printed each time. With Easy Printing, any cropping trimming will not be applied. It is for images taken with a digital camera, and you can specify which photos and the quantity to print. With a DPOF compatible digital camera, RAW images cannot be selected for printing. The order screen will appear. Select the image to be printed. Turn the dial to select the image to be printed. Press the. Otherwise, leave the box unchecked.

Press to checkmark the box, or press again to remove the checkmark. If there are other images you want to select, repeat steps 2 and 3. For standardtype prints, a quantity of one will be ordered for all

the images. Note that after following the “Selecting Individual Images” procedure, if you do the “Selecting All Images”. PictBridge Prepare to print. See “Setting the Camera” steps 1 and 2 and “Connect the camera to the printer” steps 1 to 5 on pages 123 to 124. With PictBridge, the file No.Also, Custom Functions enable you to finetune your camera to suit your shooting preferences. Custom Functions work in all modes except Full Auto. Customizing the Camera. Set the shooting mode to any mode except Full Auto. The camera settings cannot be registered in the Full Auto mode. Shooting settings Shooting mode and settings, AF mode, AF point selection, Metering mode, ISO speed, Drive mode, Exposure compensation, Flash exposure. Description Even if the C.Fn00 focusing screen setting is changed from C.Fn000 to something else, will not be displayed on the LCD panel. When the shooting mode is, the camera settings and Custom Function settings cannot be reset or cleared to the default settings. Recommended when it is bothersome to see it light up. The AF point will still light when you select it. C.Fn11 When you press the. Since automatic flash exposure compensation will not be executed, you may have to set it yourself depending on the scene. Therefore, seven AF points will track the subject p.76. While the button is pressed, AF operation with the camera is disabled. 2 AE lock while metering When the button is pressed while metering is still active, AE lock is applied. This Custom Function must be set so that the exposure correction matches the respective focusing screen. 0 EeA 1 EeD 2 EeS About focusing screen characteristics EeA Standard Precision Matte Standard focusing screen that comes with the camera.

It covers information on camera features, system accessories, and other reference information. When focus is achieved, it is locked. With evaluative uSingle metering, the exposure shooting setting is also locked. The exposure setting is stored in memory before the shot is taken. The above conditions. The combinations of shutter speed and aperture value automatically determined by Program AE are shown as lines with respect to the subject brightness Exposure Value gradations on the left and top edges of the graph. If this Troubleshooting Guide does not resolve the problem, contact your dealer or nearest Canon Service Center. Power Source The battery cannot be recharged. You are using the wrong battery. Auto power off is in effect. Press the shutter button halfway. You are using a nonCanon CF card. Press the shutter button halfway or remove and reinstall the Err 99 battery. This error may occur if you use a nonCanon lens and the camera or lens does not operate properly. Countermeasures. AC Adapter Kit ACKE2 Power source kit AC adapter, DC coupler, power cord for supplying power to the camera with a household power outlet. Compatible with 100 240 V AC. Compact Power Adapter CAPS400 Quick charger for BP511A. CF card Data storage media where the captured images are recorded. CF cards made by Canon are recommended. The camera’s specifications and physical appearance are subject to change without notice. The cable with the ferrite core provided with the digital camera must be used with this equipment in order to comply with Class B limits in Subpart B of Part 15 of the FCC rules. Upon completion of the download, the PDF file opens automatically. You may download and use the Content solely for your personal, noncommercial use and at your own risks. Canon shall not be held liable for any damages whatsoever in connection with the Content, including, without limitation, indirect, consequential, exemplary or incidental damages.

You shall also not and shall not let others reproduce, modify, reformat or create derivative works from the Content, in whole or in part. You may download and use the Content solely for your personal, noncommercial use and at your own risks. Canon shall not be held liable for any damages whatsoever in connection with the Content, including, without limitation, indirect, consequential, exemplary or incidental damages. You shall also not and shall not let others reproduce, modify, reformat or create derivative works from the Content, in whole or in part. EOS M and EOS R Full Frame mirrorless ranges deliver the power of DSLR in the body of a compact camera. Register your product and opt in for exclusive offers and discounts. Our payment security system encrypts your information during transmission. We don’t share your credit card details with thirdparty sellers, and we don’t sell your information to others. Please try again. Please try again. Then you can start reading

Kindle books on your smartphone, tablet, or computer no Kindle device required. In order to navigate out of this carousel please use your heading shortcut key to navigate to the next or previous heading. Register a free business account If you are a seller for this product, would you like to suggest updates through seller support To calculate the overall star rating and percentage breakdown by star, we don't use a simple average. Instead, our system considers things like how recent a review is and if the reviewer bought the item on Amazon. It also analyzes reviews to verify trustworthiness. Please try again later. Amazon Customer 1.0 out of 5 stars Although this is a nice printed copy that is a little smaller and about twice as thick as the factory original. Also, some information is missing in this manual that is in the real 5D Mark III manual. Attached photos of actual Original manual on right compared to this on on the left.

It looks more like a sloppy photocopy than anything resembling the Canon EOS 5D Mark III Original Instruction Manual. Avoid. Canon 5D vs. Nikon D3 28 July 2008. The 5D wins! The images look fantastic, and it runs forever on a single charge. Unlike pro cameras, its light enough to want to take in your backpack everywhere to bring back extraordinary images. Heres a snapshot made on the lowest JPG setting. Click the image for the original 12MP file from my 5D. Today, this 5D is a steal used. I thought the rebate signaled a new model, but I was wrong and lucked out. This all comes from the Full Frame Advantage. Bigger sensors or film easily make for higher technical quality images. If you want a 5D, I wouldnt wait around. Fall 2007 colors are here, and my 5D is the best Ive got before the leaves blow off the trees. Of course none of this matters unless you get the far more important basics of lighting and composition out of the way first, and then it only matters if you print large and look too closely, but for those of you who care, just get a 5D. I like this because it matches Fuji Velvia when Im shooting both at the same time. It has no Auto ISO, so I have to jack the ISO around manually for each shot, although I can do it without removing my eye from the finder. My D200 fits like a glove, while my fingers hurt after holding the 5D for any length of time. For instance, I have to use a second hand to hit the depthofield preview since its on the wrong side. Its easy to shoot my Nikons with one hand, but difficult and painful to try to do the same with my 5D. Colors look like crap on my 5Ds LCD, so I have to guess while shooting. Colors desaturate as they get brighter on the LCD, even though the actual recorded image is fine. Its as if the video circuitry is clipping the highlights of each channel before they get to the LCD; Ill have to experiment but whatever the reason, its much worse than the Canon point and shoots.